

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p><u>WAGO 2-CONDUCTOR FEMALE CONNECTOR; LOCKING LEVER; 2.5 MM²; PIN SPACING 7.62 MM; 2-POLE; 2,50 MM²; ORANGE</u></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 500; V Tensiune nominala de supratensiune (III/3): 6; kV Tensiune nominala (III/2): 630; V Tensiune nominala de supratensiune (III/2): 6; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 6; kV Curent nominal: 16; A Legend (ratings): (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 20; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 20; A Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 15; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm²; Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch; Numar poli: 2; Numar total de conexiuni: 4; Total number of potentials: 2; Numar tipuri de conexiuni: 1; Numar nivele: 1; Conductor entry direction to mating direction: 0; ° Distanta intre pini: 7.62 mm / 0.3 inch; Latime: 29.5 mm / 1.161 inch; Inaltime: 20.8 mm / 0.819 inch; Adancime: 29.8 mm / 1.173 inch; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for conductors; Mismating protection: No; Locking of plug-in connection: locking lever; Culoare: orange; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Fire load: 0,141; MJ Greutate: 6,7; g Temperatura lucru: -60 ... +85 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4044918564366; Customs tariff number: 85366990990; Pret: 13,50 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/2-conductor-female-connector-locking-lever-2-5-mm2-pin-spacing-7-62-mm-2-pole-2-50-mm2-orange-138805</p>
--	---