

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO 2-CONDUCTOR FEMALE CONNECTOR; 2.5 MM²; PIN SPACING 5 MM; 11-POLE; 2,50 MM²; GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 320; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 20; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 20; A Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 15; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm²; Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch; Numar poli: 11; Numar total de conexiuni: 22; Total number of potentials: 11; Numar tipuri de conexiuni: 1; Numar nivele: 1; Conductor entry direction to mating direction: 0; ° Distanta intre pini: 5 mm / 0.197 inch; Latime: 55 mm / 2.165 inch; Inaltime: 20.8 mm / 0.819 inch; Adancime: 26.45 mm / 1.041 inch; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for conductors; Mismatching protection: No; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Fire load: 0,392; MJ Greutate: 24,3; g Temperatura lucru: -60 ... +85 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4044918563192; Customs tariff number: 85366990990; Pret: 61,49 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/2-conductor-female-connector-2-5-mm2-pin-spacing-5-mm-11-pole-2-50-mm2-gray-138932</p>
--	---