

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO GROUND CONDUCTOR FEEDTHROUGH TERMINAL BLOCK;
CONDUCTOR/SOLDER/CRIMP QUICK DISCONNECT TERMINAL;
PLATE THICKNESS: 1.5 MM; 4 MM²; PIN SPACING 6 MM; 1-POLE;
CAGE CLAMP®; 4,00 MM²; GREEN-YELLOW**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 320; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tensiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Tensiune nominala UL (Use Group C): 300; V
Tensiune nominala UL (Use Group D): 600; V
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Tensiune nominala CSA (Use Group C): 300; V
Tensiune nominala CSA (Use Group D): 600; V
Tehnologie conexiune: CAGE CLAMP®;
Number of connection points (connection type): 1;
Tip actionare: Operating tool;
Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 ... 2,5 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²;
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;
Numar poli: 1;
Number of connection points: 1;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Ground function: with direct ground contact;
Distanta intre pini: 6 mm / 0.236 inch;
Latime: 6 mm / 0.236 inch;
Inaltime: 38,5 mm / 1.516 inch;
Inaltime de la fata: 22 mm / 0.866 inch;
Adancime: 26 mm / 1.024 inch;
Housing sheet thickness: 1,5 ... 1,5 mm / 0.059 ... 0.059 inch;
Direct ground contact to DIN-rail/drilled hole/housing: 1;
Tip montaj: Snap-in mounting foot;
Tip montaj: Feed-through mounting;
Culoare: green-yellow;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic (ECu);
Contact plating: tin-plated;
Fire load: 0,055; MJ
Greutate: 3,6; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
GTIN: 4017332107075;
Pret: 28,59 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ground-conductor-feedthrough-terminal-block-conductor-solder-crimp-quick-disconnect-terminal-plate-thickness-1-5-mm-4-mm2-pin-spacing-6-mm-1-pole-cage-clamp-4-00-mm2-green-yellow-139054>