

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

<p>Technical drawing showing top, side, and cross-sectional views of the WAGO THT Male Header. Dimensions include: L (total length), 7.5 mm (pin spacing), 3.6 mm (pin height), 2.6 mm (pin diameter), 6 mm (pin diameter), 7 mm (pin diameter), 14.4 mm (mounting flange height), 19.5 mm (total height), 16.1 mm (height to top of clamping collar), 16.8 mm (height to bottom of clamping collar), 3.4 mm (clamping collar thickness), and 3.5 mm (height to top of clamping collar).</p>	<p><b><u>WAGO THT MALE HEADER; 1.4 MM <math>\tilde{\sim}</math> SOLDER PIN; STRAIGHT; CLAMPING COLLAR; PIN SPACING 7.5 MM; 4-POLE; LIGHT GRAY</u></b></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 400; V Tensiune nominala de supratensiune (III/3): 6; kV Tensiune nominala (III/2): 630; V Tensiune nominala de supratensiune (III/2): 6; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 6; kV Curent nominal: 16; A Legend (ratings): (III / 2) <math>\hat{\sim}</math>™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Numar poli: 4; Total number of potentials: 4; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 7,5 mm / 0.295 inch; Latime: 41,7 mm / 1.642 inch; Inaltime: 23,1 mm / 0.909 inch; Inaltime de la fata: 19,5 mm / 0.768 inch; Adancime: 14,4 mm / 0.567 inch; Lungimea pinului de contact: 3,6; mm Diametrul pinului de contact: 1,4; mm Diametrul de gaurire cu toleranta: 1,6 (+0,1) mm; Tip montaj: Mounting flange; Tip montaj: Feed-through mounting; Panel mounting; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCB; Mismatching protection: No; Mating direction to the PCB: 90; ° Locking of plug-in connection: Locking latch; PCB contact: THT; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,08; MJ Greutate: 3,5; g Temperatura lucru: -60 ... +100 °C; Product Group: 26 (picoMAX); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821165873; Customs tariff number: 85366990990; Pret: 8,12 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/tht-male-header-1-4-mm-oe-solder-pin-straight-clamping-collar-pin-spacing-7-5-mm-4-pole-light-gray-139682">https://www.materialelectrice.ro/tht-male-header-1-4-mm-oe-solder-pin-straight-clamping-collar-pin-spacing-7-5-mm-4-pole-light-gray-139682</a></p>
--	---