

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO THR MALE HEADER; 1.4 MM Ø SOLDER PIN; STRAIGHT; PIN SPACING 7.5 MM; 3-POLE; LIGHT GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;                  Tensiune nominala (III/3): 400; V                  Tensiune nominala de supratensiune (III/3): 6; kV                  Tensiune nominala (III/2): 630; V                  Tensiune nominala de supratensiune (III/2): 6; kV                  Tensiune nominala (II/2): 1000; V                  Tensiune nominala de supratensiune (II/2): 6; kV                  Curent nominal: 16; A                  Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2;                  Tensiune nominala UL (Use Group B): 300; V                  Curent nominal UL (Use Group B): 15; A                  Tensiune nominala UL (Use Group D): 300; V                  Curent nominal UL (Use Group D): 10; A                  Certificari: UL 1059;                  Numar poli: 3;                  Total number of potentials: 3;                  Numar tipuri de conexiuni: 1;                  Numar nivele: 1;                  Distanta intre pini: 7,5 mm / 0.295 inch;                  Latime: 22,2 mm / 0.874 inch;                  Inaltime: 21,9 mm / 0.862 inch;                  Inaltime de la fata: 19,5 mm / 0.768 inch;                  Adancime: 14,4 mm / 0.567 inch;                  Lungimea pinului de contact: 2,4; mm                  Diametrul pinului de contact: 1,4; mm                  Diametru placat prin gaura (THR): 1,6 (+0,1) mm;                  Tip contact (pluggable connector): Conector tata/fisa;                  Connector (connection type): for PCB;                  Mismatching protection: No;                  Mating direction to the PCB: 90; °                  Locking of plug-in connection: Locking latch;                  PCB contact: THR;                  Culoare: light gray;                  Material group: I;                  Material izolator: Polyphthalamide (PPA GF);                  Flammability class per UL94: V0;                  Contact material: Cupru electrolitic(ESu);                  Contact plating: tin-plated;                  Fire load: 0,053; MJ                  Greutate: 2,4; g                  Temperatura lucru: -60 ... +100 °C;                  Tip ambalare: BOX;                  Tara de origine: DE;                  GTIN: 4050821396529;                  Customs tariff number: 85366990990;                  Pret: 5,01 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-straight-pin-spacing-7-5-mm-3-pole-light-gray-139686">https://www.materialelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-straight-pin-spacing-7-5-mm-3-pole-light-gray-139686</a></p>
--	--