

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p>WAGO SOLDER PIN STRIP; 1.4 MM $\bar{\sim}$ SOLDER PIN; ANGLED; PIN SPACING 5 MM; 12-POLE; BLACK</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) $\hat{\%}$™ Overvoltage category III / Pollution degree 2; Certificari: UL 1059; Numar poli: 12; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 5 mm / 0.197 inch; Latime: 63.2 mm / 2.488 inch; Inaltime: 7.6 mm / 0.299 inch; Inaltime de la fata: 4 mm / 0.157 inch; Adancime: 12.3 mm / 0.484 inch; Lungimea pinului de contact: 3,6; mm Diametrul pinului de contact: 1,4; mm Diametrul de gaurire cu toleranta: 1.6 (+0.1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCBs; Mismatching protection: No; Mating direction to the PCB: 0; ° PCB contact: THT; Culoare: black; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Greutate: 3,3; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: bag; Tara de origine: CN; GTIN: 4055143934695; Customs tariff number: 85369010000; Pret: 11,16 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/solder-pin-strip-1-4-mm-oe-solder-pin-angled-pin-spacing-5-mm-12-pole-black-139738</p>
--	--