

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO SOLDER PIN STRIP; 1.4 MM <math>\tilde{\sim}</math> SOLDER PIN; ANGLED; PIN SPACING 5 MM; 6-POLE; BLACK</b></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) <math>\hat{\sim}</math>™ Overvoltage category III / Pollution degree 2; Certificari: UL 1059; Numar poli: 6; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 5 mm / 0.197 inch; Latime: 33.2 mm / 1.307 inch; Inaltime: 7.6 mm / 0.299 inch; Inaltime de la fata: 4 mm / 0.157 inch; Adancime: 12.3 mm / 0.484 inch; Lungimea pinului de contact: 3,6; mm Diametrul pinului de contact: 1,4; mm Diametrul de gaurire cu toleranta: 1.6 (+0.1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCBs; Mismatching protection: No; Mating direction to the PCB: 0; ° PCB contact: THT; Culoare: black; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Greutate: 1,7; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: bag; Tara de origine: CN; GTIN: 4055143935029; Customs tariff number: 85369010000; Pret: 5,61 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/solder-pin-strip-1-4-mm-oe-solder-pin-angled-pin-spacing-5-mm-6-pole-black-139755">https://www.materialelectrice.ro/solder-pin-strip-1-4-mm-oe-solder-pin-angled-pin-spacing-5-mm-6-pole-black-139755</a></p>
--	---