

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p align="center"><u>WAGO THR MALE HEADER; 1.4 MM Å SOLDER PIN; ANGLED; IN TAPE-AND-REEL PACKAGING; PIN SPACING 5 MM; 3-POLE; LIGHT GRAY</u></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Total number of potentials: 3; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 5 mm / 0.197 inch; Latime: 17.2 mm / 0.677 inch; Inaltime: 16.8 mm / 0.661 inch; Inaltime de la fata: 14.4 mm / 0.567 inch; Adancime: 19.5 mm / 0.768 inch; Lungimea pinului de contact: 2,4; mm Diametrul pinului de contact: 1,4; mm Diametru placat prin gaura (THR): 1.6 (+0.1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCBs; Mismatching protection: No; Mating direction to the PCB: 0; ° Locking of plug-in connection: Male locking latch; PCB contact: THR; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Greutate: 5,8; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: bag; Tara de origine: DE; GTIN: 4055143934657; Customs tariff number: 85366990990; Pret: 5,97 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-angled-in-tape-and-reel-packaging-pin-spacing-5-mm-3-pole-light-gray-139833</p>
--	---