

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p align="center"><b><u>WAGO THR MALE HEADER; 1.4 MM <math>\tilde{\sim}</math> SOLDER PIN; ANGLED; CLAMPING COLLAR; PIN SPACING 5 MM; 2-POLE; LIGHT GRAY</u></b></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) <math>\hat{\sim}</math>™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Numar poli: 2; Total number of potentials: 2; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 5 mm / 0.197 inch; Latime: 24,2 mm / 0.953 inch; Inaltime: 16,8 mm / 0.661 inch; Inaltime de la fata: 14,4 mm / 0.567 inch; Adancime: 19,5 mm / 0.768 inch; Lungimea pinului de contact: 2,4; mm Diametrul pinului de contact: 1,4; mm Diametru placat prin gaura (THR): 1,6 (+0,1) mm; Tip montaj: Mounting flange; Tip montaj: Feed-through mounting; Panel mounting; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCB; Mismatching protection: No; Mating direction to the PCB: 0; ° Locking of plug-in connection: Locking latch; PCB contact: THR; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,049; MJ Greutate: 2; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821395812; Customs tariff number: 85366990990; Pret: 4,66 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-angled-clamping-collar-pin-spacing-5-mm-2-pole-light-gray-139837">https://www.materialelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-angled-clamping-collar-pin-spacing-5-mm-2-pole-light-gray-139837</a></p>
--	---