


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO TRIPLE-DECK TERMINAL BLOCK;  
THROUGH/THROUGH/THROUGH TERMINAL BLOCK; L/L/L; WITHOUT  
MARKER CARRIER; SUITABLE FOR EX E II APPLICATIONS; FOR DIN-  
RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®;  
2,50 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 24; A  
Curent nominal 2: 28; A  
Legend (ratings): (III / 3) %<sup>o</sup>™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL (Use Group B): 300; V  
Curent nominal UL (Use Group B): 20; A  
Tensiune nominala UL (Use Group C): 300; V  
Curent nominal UL (Use Group C): 20; A  
Tensiune nominala UL (Use Group D): 600; V  
Curent nominal UL (Use Group D): 5; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group B): 600; V  
Curent nominal CSA (Use Group B): 20; A  
Tensiune nominala CSA (Use Group C): 600; V  
Curent nominal CSA (Use Group C): 20; A  
Tensiune nominala EN (Ex e II): 440; V  
Curent nominal (Ex e II): 19; A  
Curent nominal (Ex e II) with jumper: 17; A  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Number of connection points (connection type): 3;  
Tip actionare: Push-in; Open Tool Slot;  
Connectable conductor materials: Copper;  
Nominal cross-section: 2,5 mm<sup>2</sup>;  
Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;  
Number of connection points: 3;  
Numar total de conexiuni: 6;  
Total number of potentials: 3;  
Numar nivele: 3;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Latime: 5,2 mm / 0.205 inch;  
Inaltime from upper-edge of DIN-rail: 69,5 mm / 2.736 inch;  
Adancime: 93,3 mm / 3.673 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Potential marking: L/L/L;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,316; MJ  
Greutate: 16,8; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918691185;  
Customs tariff number: 85369010000;  
Pret: 19,15 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/triple-deck-terminal-block-through-through-through-terminal-block-l-l-l-without-marker-carrier-suitable-for-ex-e-ii-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-139888>