

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p>WAGO SMD PCB TERMINAL BLOCK; 0.5 MM²; PIN SPACING 3 MM; 1-POLE; PUSH WIRE[®]; IN TAPE-AND-REEL PACKAGING; 0,50 MM²; WHITE</p> <p>Ratings per: IEC/EN 60664-1; Tesiune nominala (III/3): 63; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tesiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 3; A Legend (ratings): (III / 2) %TM Overvoltage category III / Pollution degree 2; Certificari: UL 1059; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 3; A Tehnologie conexiune: PUSH WIRE[®]; Tip actionare: Operating tool; Solid conductor: 0,14 ... 0,34 mm² / 26 ... 22 AWG; Strip length: 4 ... 5,5 mm / 0.16 ... 0.22 inch; Conductor connection direction to PCB: 0; ° Numar poli: 1; Solid conductor 2: 0,5 mm² / 20 AWG; Note (conductor cross-section) 2: No reconnection of smaller conductor cross-sections (0.5 mm²/20 AWG); Strip length 2: 6 ... 7,5 mm / 0.24 ... 0.3 inch; Numar total de conexiuni: 1; Total number of potentials: 1; Numar tipuri de conexiuni: 1; Numar nivele: 1; Note (conductor cross-section): For conductors (26 AWG) that are not rigid enough, the clamping unit must be opened using an operating tool.; Distanta intre pini: 3 mm / 0.118 inch; Latime: 2,9 mm / 0.114 inch; Inaltime: 2,7 mm / 0.106 inch; Adancime: 7,9 mm / 0.311 inch; Reel diameter of tape-and-reel packaging: 330; mm Tape Latime: 16; mm PCB contact: SMD; Culoare: white; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Greutate: 0,1; g Temperatura lucru: -60 ... +105 °C; Product Group: 33 (Printed Circuit); Tip ambalare: BOX; Tara de origine: CH; GTIN: 4055143082679; Customs tariff number: 85369010000; Pret: 1,85 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/smd-pcb-terminal-block-0-5-mm2-pin-spacing-3-mm-1-pole-push-wire-in-tape-and-reel-packaging-0-50-mm2-white-139910</p>
--	---