

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

**WAGO SMD PCB TERMINAL BLOCK; 0.5 MM²; PIN SPACING 3 MM;
 2-POLE; PUSH WIRE[®]; IN TAPE-AND-REEL PACKAGING; 0,50
 MM²; WHITE**

Ratings per: IEC/EN 60664-1;
 Tesiune nominala (III/3): 63; V
 Tensiune nominala de supratensiune (III/3): 2,5; kV
 Tensiune nominala (III/2): 160; V
 Tensiune nominala de supratensiune (III/2): 2,5; kV
 Tensiune nominala (II/2): 320; V
 Tensiune nominala de supratensiune (II/2): 2,5; kV
 Curent nominal: 3; A
 Legend (ratings): (III / 2) $\hat{\%}$ ™ Overvoltage category III / Pollution degree 2;
 Certificari: UL 1059;
 Tensiune nominala UL 1977: 250; V
 Curent nominal UL 1977: 3; A
 Tehnologie conexiune: PUSH WIRE[®];
 Tip actionare: Operating tool;
 Solid conductor: 0,14 ... 0,34 mm² / 26 ... 22 AWG;
 Strip length: 4 ... 5,5 mm / 0.16 ... 0.22 inch;
 Conductor connection direction to PCB: 0; °
 Numar poli: 2;
 Solid conductor 2: 0,5 mm² / 20 AWG;
 Note (conductor cross-section) 2: No reconnection of smaller conductor cross-sections
 (0.5 mm²/20 AWG);
 Strip length 2: 6 ... 7,5 mm / 0.24 ... 0.3 inch;
 Numar total de conexiuni: 2;
 Total number of potentials: 2;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 1;
 Note (conductor cross-section): For conductors (26 AWG) that are not rigid enough, the
 clamping unit must be opened using an operating tool.;
 Distanta intre pini: 3 mm / 0.118 inch;
 Latime: 5,9 mm / 0.232 inch;
 Inaltime: 2,7 mm / 0.106 inch;
 Adancime: 7,9 mm / 0.311 inch;
 Reel diameter of tape-and-reel packaging: 330; mm
 Tape Latime: 16; mm
 PCB contact: SMD;
 Culoare: white;
 Material group: I;
 Material izolator: Polyphthalamide (PPA GF);
 Flammability class per UL94: V0;
 Clamping spring material: Chrome nickel spring steel (CrNi);
 Contact material: Copper alloy;
 Contact plating: tin-plated;
 Greutate: 0,2; g
 Temperatura lucru: -60 ... +105 °C;
 Product Group: 33 (Printed Circuit);
 Tip ambalare: BOX;
 Tara de origine: CH;
 GTIN: 4055143082686;
 Customs tariff number: 85369010000;
 Pret: 2,63 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/smd-pcb-terminal-block-0-5-mm2-pin-spacing-3-mm-2-pole-push-wire-in-tape-and-reel-packaging-0-50-mm2-white-139933>