

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 1.5 MM²;
SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER
MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE
CLAMP®; 1,50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 18; A
Curent nominal 2: 24; A
Legend (ratings): (III / 3) %TM Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group B): 600; V
Curent nominal UL (Use Group B): 15; A
Tensiune nominala UL (Use Group C): 600; V
Curent nominal UL (Use Group C): 15; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 600; V
Curent nominal CSA (Use Group B): 15; A
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 15; A
Tensiune nominala EN (Ex e II): 550; V
Curent nominal (Ex e II): 17; A
Curent nominal (Ex e II) with jumper: 16; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 1,5 mm²;
Solid conductor: 0,25 ... 2,5 mm² / 22 ... 14 AWG;
Solid conductor; push-in termination: 0,75 ... 2,5 mm² / 18 ... 14 AWG;
Fine-stranded conductor: 0,25 ... 2,5 mm² / 22 ... 14 AWG;
Fine-stranded conductor; with insulated ferrule: 0,75 ... 1,5 mm² / 18 ... 16 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0,75 ... 1,5 mm² / 18 ... 16 AWG;
Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 4,2 mm / 0.165 inch;
Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;
Adancime: 48,5 mm / 1.909 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 3,9; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4017332997287;
Customs tariff number: 85369010000;
Pret: 4,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-1-5-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-1-50-mm2-gray-139945>