


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

| | |
|---|---|
|  | <p>WAGO MULTILEVEL INSTALLATION TERMINAL BLOCK; 4 MM²; L/L/PE; PUSH-IN CAGE CLAMP®; 2,50 MM²; GRAY</p> <p>Ratings (note): Potential - ground; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 32; A Ratings (note) 2: Potential - potential; Tensiune nominala (III/3) 2: 400; V Tensiune nominala de supratensiune (III/3) 2: 6; kV Curent nominal 2: 32; A Legend (ratings): (III / 3) % Overvoltage category III / Pollution degree 3; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-in; Open Tool Slot; Connectable conductor materials: Copper; Nominal cross-section: 2,5 mm²; Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG; Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG; Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG; Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG; Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch; Numar total de conexiuni: 5; Total number of potentials: 3; Numar nivele: 3; Wiring type: Front-entry wiring; Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.; Latime: 5,2 mm / 0.205 inch; Inaltime from upper-edge of DIN-rail: 42,3 mm / 1.665 inch; Adancime: 96 mm / 3.78 inch; Design: angled; Tip montaj: DIN-35 rail; Potential marking: L/L/PE; Marking level: Center/side marking; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Fire load: 0,245; MJ Greutate: 16,3; g Product Group: 22 (TOPJOB S); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4044918925600; Customs tariff number: 85369010000; Pret: 15,21 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/multilevel-installation-terminal-block-4-mm2-l-l-pe-push-in-cage-clamp-2-50-mm2-gray-139961</p> |
|---|---|