

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 10 MM<sup>2</sup>;  
SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER  
MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE  
CLAMP®; 10,00 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Push-in; Open Tool Slot;  
Connectable conductor materials: Copper;  
Nominal cross-section: 10 mm<sup>2</sup>;  
Solid conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;  
Solid conductor; push-in termination: 4 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;  
Fine-stranded conductor: 0,5 ... 16 mm<sup>2</sup> / 20 ... 6 AWG;  
Fine-stranded conductor; with insulated ferrule: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 4 ... 10 mm<sup>2</sup> / 12 ... 8 AWG;  
Strip length: 17 ... 19 mm / 0.67 ... 0.75 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Number of jumper slots: 2;  
Latime: 10 mm / 0.394 inch;  
Inaltime from upper-edge of DIN-rail: 36,9 mm / 1.453 inch;  
Adancime: 67,8 mm / 2.669 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,273; MJ  
Greutate: 30,1; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4017332076180;  
Customs tariff number: 85369010000;  
Pret: 26,04 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-ground-terminal-block-10-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-10-00-mm2-green-yellow-139986>