


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 3-CONDUCTOR, DOUBLE-DECK TERMINAL BLOCK; 6-
CONDUCTOR THROUGH TERMINAL BLOCK; N; SUITABLE FOR EX I
APPLICATIONS; INTERNAL COMMONING; CONDUCTOR ENTRY WITH
VIOLET MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²;
CAGE CLAMP®; 2.50 MM²; BLUE**

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 24; A
Legend (ratings): (III / 3) %TM Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;
Numar total de conexiuni: 6;
Total number of potentials: 1;
Numar nivele: 2;
Wiring type: Front-entry wiring;
Latime: 5 mm / 0.197 inch;
Inaltime from upper-edge of DIN-rail: 40 mm / 1.575 inch;
Adancime: 91 mm / 3.583 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Potential marking: N;
Marking level: Side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,205; MJ
Greutate: 14,4; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454094546;
Customs tariff number: 85369010000;
Pret: 23,58 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-double-deck-terminal-block-6-conductor-through-terminal-block-n-suitable-for-ex-i-applications-internal-commoning-conductor-entry-with-violet-marking-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-blue-141361>