

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR CENTER TERMINAL BLOCK; SUITABLE FOR  
EX I APPLICATIONS; WITHOUT PUSH-BUTTONS; 2.5 MM<sup>2</sup>; CAGE  
CLAMP®; 2,50 MM<sup>2</sup>; BLUE**

Tesiune nominala (III/3): 800; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 24; A  
Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Latime: 10 mm / 0.394 inch;  
Inaltime de la fata: 22,1 mm / 0.87 inch;  
Adancime: 32 mm / 1.26 inch;  
Design: horizontal type;  
Tip montaj: Mounting flange;  
Marking level: Center marking;  
Culoare: blue;  
Fire load: 0,112; MJ  
Greutate: 6,4; g  
Product Group: 9 (Std. Chassis Mt. Blocks);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4044918414777;  
Customs tariff number: 85369010000;  
Pret: 6,81 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-center-terminal-block-suitable-for-ex-i-applications-without-push-buttons-2-5-mm2-cage-clamp-2-50-mm2-blue-141587>