


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR CLASS CC  
FUSES; 2-POLE; WITH BLOWN FUSE INDICATION; FOR DIN-RAIL 35  
X 15 AND 35 X 7.5; 16 MM<sup>2</sup>; CAGE CLAMP<sup>®</sup>; 16,00 MM<sup>2</sup>; LIGHT  
GRAY**

Voltage type 1: AC;  
Voltage type 2: DC;  
Ratings per: IEC/EN 60947-7-3;  
Tesiune nominala (III/3): 600; V  
Curent nominal: 32; A  
Tensiune nominala (III/3) 2: 600; V  
Tehnologie conexiune: CAGE CLAMP<sup>®</sup>;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 2,5 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;  
Fine-stranded conductor: 2,5 ... 16 mm<sup>2</sup> / 16 ... 6 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Numar poli: 2;  
Numar total de conexiuni: 4;  
Total number of potentials: 2;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 35 mm / 1.378 inch;  
Inaltime from upper-edge of DIN-rail: 55 mm / 2.165 inch;  
Adancime: 105 mm / 4.134 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Culoare: light gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 1,1; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
GTIN: 4050821508281;  
Pret: 302,85 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-fuse-terminal-block-for-class-cc-fuses-2-pole-with-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-16-mm2-cage-clamp-16-00-mm2-light-gray-141612>