

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR MINIATURE THROUGH TERMINAL BLOCK; 2.5  
MM<sup>2</sup>; WITH TEST OPTION; SUITABLE FOR EX E II APPLICATIONS;  
CENTER MARKING; FOR DIN-15 RAIL; CAGE CLAMP®; 2,50 MM<sup>2</sup>;  
LIGHT GRAY**

Tensiune nominala EN (Ex e II): 690; V  
Curent nominal (Ex e II): 23; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,5 ... 2,5 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Latime: 10 mm / 0.394 inch;  
Inaltime from upper-edge of DIN-rail: 24,5 mm / 0.965 inch;  
Adancime: 32 mm / 1.26 inch;  
Design: horizontal;  
Tip montaj: DIN-15 rail;  
Marking level: Center marking;  
Culoare: light gray;  
Fire load: 0,102; MJ  
Greutate: 6; g  
Product Group: 9 (Std. Chassis Mt. Blocks);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4044918414470;  
Customs tariff number: 85369010000;  
Pret: 6,98 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-miniature-through-terminal-block-2-5-mm2-with-test-option-suitable-for-ex-e-ii-applications-center-marking-for-din-15-rail-cage-clamp-2-50-mm2-light-gray-141717>