

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

<p>* ± 0.05 mm Drilled hole diameter: 1.5^{+0.1} mm</p>	<p align="center">WAGO SOCKET FOR PCBs; ANGLED; 4-POLE; COD. B; GRAY</p> <p>Note on Contact Resistance: approx. 1 mΩ; contact resistance ≈ approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 400; V Tensiune nominala de supratensiune (III/3): 6; kV Curent nominal: 25; A Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 23; A Numar poli: 4; Total number of potentials: 4; Numar nivele: 1; Distanta intre pini: 10 mm / 0.394 inch; Latime: 37 mm / 1.457 inch; Inaltime: 18,1 mm / 0.713 inch; Inaltime de la fata: 14,6 mm / 0.575 inch; Adancime: 26 mm / 1.024 inch; Lungimea pinului de contact: 3,5; mm Solder pin dimensions: 1 x 0,8 mm; Diametrul de gaurire cu toleranta: 1,5 (-0,1 ... +0,1) mm; Coding: B; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: Locked: > 80 N; Unmating force of a plug-in connection: Unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: >200, without resistive load 100, with resistive load IN = 25 A, tested (4 mm²/AWG 12); Design: angled; Marking: N 2/L 1/L'; Potential marking: N 2/L 1/L'; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for PCB; Mismating protection: Yes; Mating direction to the PCB: 0; ° Locking of plug-in connection: locking lever; Locking lever: yes; PCB contact: THT; Solder pin arrangement: 2 in-line solder pins/pole; Number of solder pins per potential: 2; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper or copper alloy (surface-treated); Fire load: 0,157; MJ Greutate: 8,6; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: Insulating parts for temperatures ≤ 105 °C; Tip ambalare: BOX; Tara de origine: PL; GTIN: 4050821555452; Customs tariff number: 85366990990; Pret: 14,57 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/socket-for-pcb-s-angled-4-pole-cod-b-gray-141794</p>
---	---