

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 1-CONDUCTOR/1-CONDUCTOR TERMINAL BLOCK FOR
PLUGGABLE MODULES; 6-POLE; WITH 2-CONDUCTOR TERMINAL
BLOCKS; WITH 2 JUMPER POSITIONS; WITH ORANGE SEPARATOR
PLATE; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 4 MM²; CAGE
CLAMP®; 4,00 MM²; GRAY**

Tensiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) % Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Connectable conductor materials: Copper;
Nominal cross-section: 4 mm²;
Solid conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 6;
Numar total de conexiuni: 6;
Total number of potentials: 6;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 16.1 mm / 0.634 inch;
Inaltime from upper-edge of DIN-rail: 28.5 mm / 1.122 inch;
Adancime: 87.5 mm / 3.445 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,569; MJ
Greutate: 26,7; g
Product Group: 18 (X-COM-System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918935258;
Customs tariff number: 85369010000;
Pret: 31,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-1-conductor-terminal-block-for-pluggable-modules-6-pole-with-2-conductor-terminal-blocks-with-2-jumper-positions-with-orange-separator-plate-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-141975>