


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO STACKABLE PCB TERMINAL BLOCK; 4 MM²; PIN SPACING
 10 MM; 1-POLE; CAGE CLAMP[®]; COMMONING OPTION; 4,00 MM²;
 LIGHT GREEN**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 630; V
 Tensiune nominala de supratensiune (III/3): 8; kV
 Tensiune nominala (III/2): 1000; V
 Tensiune nominala de supratensiune (III/2): 8; kV
 Tensiune nominala (II/2): 1000; V
 Tensiune nominala de supratensiune (II/2): 8; kV
 Curent nominal: 32; A
 Legend (ratings): (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 300; V
 Curent nominal UL (Use Group B): 20; A
 Tensiune nominala UL (Use Group C): 150; V
 Curent nominal UL (Use Group C): 20; A
 Tensiune nominala UL (Use Group D): 300; V
 Curent nominal UL (Use Group D): 10; A
 Certificari: UL 1059;
 Tensiune nominala CSA (Use Group B): 300; V
 Curent nominal CSA (Use Group B): 20; A
 Tensiune nominala CSA (Use Group C): 150; V
 Curent nominal CSA (Use Group C): 20; A
 Tensiune nominala CSA (Use Group D): 300; V
 Curent nominal CSA (Use Group D): 10; A
 Tehnologie conexiune: CAGE CLAMP[®];
 Tip actionare: Operating tool;
 Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
 Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 2,5 mm²;
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²;
 Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
 Conductor connection direction to PCB: 45; °
 Numar poli: 1;
 Numar total de conexiuni: 1;
 Total number of potentials: 1;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 1;
 Number of jumper slots: 1;
 Distanta intre pini: 10 mm / 0.394 inch;
 Latime: 11,5 mm / 0.453 inch;
 Inaltime: 23 mm / 0.906 inch;
 Inaltime de la fata: 19 mm / 0.748 inch;
 Adancime: 22,9 mm / 0.902 inch;
 Lungimea pinului de contact: 4; mm
 Solder pin dimensions: 0,8 x 1,2 mm;
 Diametrul de gaurire cu toleranta: 1,5 (+0,1) mm;
 PCB contact: THT;
 Solder pin arrangement: within the terminal block (in-line);
 Number of solder pins per potential: 2;
 Culoare: light green;
 Material group: I;
 Material izolator: Polyamide 66 (PA 66);
 Flammability class per UL94: V0;
 Clamping spring material: Chrome nickel spring steel (CrNi);
 Contact material: Cupru electrolitic (ECu);
 Contact plating: tin-plated;
 Fire load: 0,061; MJ
 Greutate: 3; g
 Temperatura lucru: -60 ... +105 °C;
 Product Group: 4 (Printed Circuit);
 Tip ambalare: BOX;
 Tara de origine: PL;
 GTIN: 4044918937269;
 Customs tariff number: 85369010000;
 Pret: 3,94 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/stackable-pcb-terminal-block-4-mm2-pin-spacing-10-mm-1-pole-cage-clamp-commoning-option-4-00-mm2-light-green-142031>