

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; 2-POLE;
WITHOUT GROUND CONTACT; FOR 3 MM \hat{A} , SCREW AND NUT; WITH
2X PIN; 4 MM \hat{A} ²; 4,00 MM \hat{A} ²; WHITE**

Tesiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 32; A
Legend (ratings): (III / 3) \hat{A} ™ Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Operating tool; Push-button;
Connectable conductor materials: Copper;
Solid conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;
Solid conductor; push-in termination: 0.75 ... 4 mm² / 18 ... 12 AWG;
Stranded conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;
Fine-stranded conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0.5 ... 2.5 mm² / 20 ... 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0.75 mm² / 18 AWG;
Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;
Numar poli: 2;
Numar total de conexiuni: 8;
Total number of potentials: 2;
Wiring type: Side-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Distanta intre pini: 12 mm / 0.472 inch;
Latime: 24 mm / 0.945 inch;
Inaltime de la fata: 22.3 mm / 0.878 inch;
Adancime: 35 mm / 1.378 inch;
Tip montaj: Screw mounting;
Marking: plain;
Culoare: white;
Fire load: 0,266; MJ
Greutate: 13,5; g
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4044918509411;
Customs tariff number: 85369010000;
Pret: 8,96 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-chassis-mount-terminal-strip-2-pole-without-ground-contact-for-3-mm-oe-screw-and-nut-with-2x-pin-4-mm2-4-00-mm2-white-142051>