





Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

<p>Hole patterns</p> <p>2-pole </p> <p>3-pole </p> <p>6-pole </p> <p>7-pole </p> <p>2 solder pins/pole in line</p>	<p>WAGO PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 3.81 MM; 6-POLE; PUSH WIRE[®]; 1,50 MM²; ORANGE</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 10; A Legend (ratings): (III / 2) \hat{a}%TM Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: PUSH WIRE[®]; Tip actionare: Push-button; Solid conductor: 0.5 ... 1.5 mm² / 20 ... 16 AWG; Fine-stranded conductor; with insulated ferrule: 0.5 ... 1 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.5 ... 1 mm²; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Conductor connection direction to PCB: 90; ° Numar poli: 6; Numar total de conexiuni: 6; Total number of potentials: 6; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 3.81 mm / 0.15 inch; Latime: 22.86 mm / 0.9 inch; Inaltime: 21.9 mm / 0.862 inch; Inaltime de la fata: 18.4 mm / 0.724 inch; Adancime: 10.8 mm / 0.425 inch; Lungimea pinului de contact: 3,5; mm Solder pin dimensions: 0.4 x 0.9 mm; Diametrul de gaurire cu toleranta: 1 (+0.1) mm; PCB contact: THT; Solder pin arrangement: over the entire terminal strip, in line; Number of solder pins per potential: 2; Culoare: orange; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,061; MJ Greutate: 4,7; g Temperatura lucru: -60 ... +105 °C; Product Group: 4 (Printed Circuit); Tip ambalare: BOX; Tara de origine: CH; GTIN: 4044918792752; Customs tariff number: 85369010000; Pret: 8,42 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/pcb-terminal-block-push-button-1-5-mm2-pin-spacing-3-81-mm-6-pole-push-wire-1-50-mm2-orange-142097</p>
--	---