

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO 1-CONDUCTOR FEMALE PLUG; 2.5 MM<sup>2</sup>; PIN SPACING 5 MM; 2-POLE; 2,50 MM<sup>2</sup>; LIGHT GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;                  Tensiune nominala (III/3): 250; V                  Tensiune nominala de supratensiune (III/3): 4; kV                  Tensiune nominala (III/2): 320; V                  Tensiune nominala de supratensiune (III/2): 4; kV                  Tensiune nominala (II/2): 630; V                  Tensiune nominala de supratensiune (II/2): 4; kV                  Curent nominal: 16; A                  Legend (ratings): (III / 2) <math>\hat{a}</math>%<sup>TM</sup> Overvoltage category III / Pollution degree 2;                  Tensiune nominala UL (Use Group B): 300; V                  Curent nominal UL (Use Group B): 15; A                  Tensiune nominala UL (Use Group D): 300; V                  Curent nominal UL (Use Group D): 10; A                  Certificari: UL 1059;                  Tehnologie conexiune: Push-in CAGE CLAMP®;                  Tip actionare: Push-button;                  Solid conductor: 0.2 ... 2.5 mm<sup>2</sup> / 24 ... 12 AWG;                  Fine-stranded conductor: 0.2 ... 2.5 mm<sup>2</sup> / 24 ... 12 AWG;                  Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;                  Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm<sup>2</sup>;                  Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;                  Numar poli: 2;                  Numar total de conexiuni: 2;                  Total number of potentials: 2;                  Numar tipuri de conexiuni: 1;                  Numar nivele: 1;                  Distanta intre pini: 5 mm / 0.197 inch;                  Latime: 10 mm / 0.394 inch;                  Inaltime: 16.2 mm / 0.638 inch;                  Adancime: 13.4 mm / 0.528 inch;                  Tip contact (pluggable connector): Conector mama/priza;                  Connector (connection type): for conductors;                  Mismatching protection: No;                  Culoare: light gray;                  Material group: I;                  Material izolator: Polyphthalamide (PPA GF);                  Flammability class per UL94: V0;                  Clamping spring material: Chrome nickel spring steel (CrNi);                  Contact material: Cupru electrolitic(ECu);                  Contact plating: tin-plated;                  Fire load: 0,044; MJ                  Greutate: 1,8; g                  Temperatura lucru: -60 ... +100 °C;                  Product Group: 26 (picoMAX);                  Tip ambalare: BOX;                  Tara de origine: DE;                  GTIN: 4050821163473;                  Customs tariff number: 85366990990;                  Pret: 7,46 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/1-conductor-female-plug-2-5-mm2-pin-spacing-5-mm-2-pole-2-50-mm2-light-gray-142111">https://www.materialelectrice.ro/1-conductor-female-plug-2-5-mm2-pin-spacing-5-mm-2-pole-2-50-mm2-light-gray-142111</a></p>
--	---