

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

|  |  |
|--|--|
|  | <p><b>WAGO 1-CONDUCTOR FEMALE PLUG; 2.5 MM<sup>2</sup>; PIN SPACING 5 MM;<br/>8-POLE; 2,50 MM<sup>2</sup>; LIGHT GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;<br/>Tensiune nominala (III/3): 250; V<br/>Tensiune nominala de supratensiune (III/3): 4; kV<br/>Tensiune nominala (III/2): 320; V<br/>Tensiune nominala de supratensiune (III/2): 4; kV<br/>Tensiune nominala (II/2): 630; V<br/>Tensiune nominala de supratensiune (II/2): 4; kV<br/>Curent nominal: 16; A<br/>Legend (ratings): (III / 2) <math>\hat{a}</math>%<sup>TM</sup> Overvoltage category III / Pollution degree 2;<br/>Tensiune nominala UL (Use Group B): 300; V<br/>Curent nominal UL (Use Group B): 15; A<br/>Tensiune nominala UL (Use Group D): 300; V<br/>Curent nominal UL (Use Group D): 10; A<br/>Certificari: UL 1059;<br/>Tehnologie conexiune: Push-in CAGE CLAMP®;<br/>Tip actionare: Push-button;<br/>Solid conductor: 0.2 ... 2.5 mm<sup>2</sup> / 24 ... 12 AWG;<br/>Fine-stranded conductor: 0.2 ... 2.5 mm<sup>2</sup> / 24 ... 12 AWG;<br/>Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;<br/>Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm<sup>2</sup>;<br/>Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;<br/>Numar poli: 8;<br/>Numar total de conexiuni: 8;<br/>Total number of potentials: 8;<br/>Numar tipuri de conexiuni: 1;<br/>Numar nivele: 1;<br/>Distanta intre pini: 5 mm / 0.197 inch;<br/>Latime: 40 mm / 1.575 inch;<br/>Inaltime: 16.2 mm / 0.638 inch;<br/>Adancime: 13.4 mm / 0.528 inch;<br/>Tip contact (pluggable connector): Conector mama/priza;<br/>Connector (connection type): for conductors;<br/>Mismatching protection: No;<br/>Culoare: light gray;<br/>Material group: I;<br/>Material izolator: Polyphthalamide (PPA GF);<br/>Flammability class per UL94: V0;<br/>Clamping spring material: Chrome nickel spring steel (CrNi);<br/>Contact material: Cupru electrolitic(ECu);<br/>Contact plating: tin-plated;<br/>Fire load: 0,171; MJ<br/>Greutate: 7,3; g<br/>Temperatura lucru: -60 ... +100 °C;<br/>Product Group: 26 (picoMAX);<br/>Tip ambalare: BOX;<br/>Tara de origine: DE;<br/>GTIN: 4050821163527;<br/>Customs tariff number: 85366990990;<br/>Pret: 24,90 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/1-conductor-female-plug-2-5-mm2-pin-spacing-5-mm-8-pole-2-50-mm2-light-gray-142354">https://www.materialelectrice.ro/1-conductor-female-plug-2-5-mm2-pin-spacing-5-mm-8-pole-2-50-mm2-light-gray-142354</a></p> |
|--|--|