


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><b>WAGO TRIPLE-DECK TERMINAL BLOCK; THROUGH/THROUGH/THROUGH TERMINAL BLOCK; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; GRAY/GRAY/BLUE</b></p> <p>Ratings per: IEC/EN 60947-7-1; Tesiune nominala (III/3): 500; V Tensiune nominala de supratensiune (III/3): 6; kV Curent nominal: 20; A Legend (ratings): (III / 3) %<sup>TM</sup> Overvoltage category III / Pollution degree 3; Tehnologie conexiune: CAGE CLAMP®; Tip actionare: Operating tool; Connectable conductor materials: Copper; Aluminum; Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG; Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Numar total de conexiuni: 6; Total number of potentials: 3; Numar nivele: 3; Wiring type: Front-entry wiring; Note (conductor cross-section): 12 AWG: THHN, THWN; Latime: 5 mm / 0.197 inch; Inaltime from upper-edge of DIN-rail: 76,5 mm / 3.012 inch; Adancime: 103 mm / 4.055 inch; Design: horizontal type; Tip montaj: DIN-35 rail; Marking level: Center marking; Culoare: gray/gray/blue; Material izolator: Polyamide 66 (PA 66); Fire load: 0,277; MJ Greutate: 18,4; g Product Group: 1 (Rail Mounted Terminal Blocks); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4044918543323; Customs tariff number: 85369010000; Pret: 23,62 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/triple-deck-terminal-block-through-through-through-terminal-block-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-gray-blue-142366">https://www.materialelectrice.ro/triple-deck-terminal-block-through-through-through-terminal-block-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-gray-blue-142366</a></p>
---	---