

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO TAP-OFF MODULE; FOR FLAT CABLE; 5 X 2.5 MM² + 2 X 1.5
MM²; 2-POLE; COD. E; GREEN**

Note on Contact Resistance: approx. 1 mΩ; of contact resistance ≈ approx. 0.25 mΩ;
contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 50; V
Tensiune nominala de supratensiune (III/3): 0,8; kV
Curent nominal: 3; A
Legend (ratings): (III / 3) % Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: IDC;
Tip actionare: Operating tool;
Numar poli: 2;
Latime: 39,4 mm / 1.551 inch;
Inaltime: 25 mm / 0.984 inch;
Adancime: 44 mm / 1.732 inch;
Tehnologie: KNX;
Coding: E;
Mating force of a plug-in connection: approx. 10 ... 15 N;
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;
Number of mating cycles: >200;
Marking: 1+ 2-;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed
for use in open, easily accessible areas).;
Potential marking: 1+ 2-;
Application: KNX;
Suitable: for flat cable 5 x 2.5 mm² + 2 x 1.5 mm²;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: green;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Greutate: 19,6; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C
(including halogen-free) PVC flat cable for temperatures -15 °C to ≤ 70 °C (including
halogen-free) Insulating parts for temperatures ≤ 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454267292;
Customs tariff number: 85366990990;
Pret: 102,68 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/tap-off-module-for-flat-cable-5-x-2-5-mm2-2-x-1-5-mm2-2-pole-cod-e-green-142368>