


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO COMPONENT TERMINAL BLOCK; 4-CONDUCTOR; WITH  
DIODE 1N5408; ANODE, LEFT SIDE; FOR DIN-RAIL 35 X 15 AND 35 X  
7.5; 4 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 4,00 MM<sup>2</sup>; GRAY**

Tesiune nominala: 250; V  
Reverse voltage: 1.000; V  
Ratings per: IEC/EN 60947-7-1;  
Curent nominal: 1,5; A  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Push-in; Open Tool Slot;  
Connectable conductor materials: Copper;  
Nominal cross-section: 4 mm<sup>2</sup>;  
Solid conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;  
Solid conductor; push-in termination: 1,5 ... 6 mm<sup>2</sup> / 14 ... 10 AWG;  
Fine-stranded conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;  
Fine-stranded conductor; with insulated ferrule: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;  
Latime: 6,2 mm / 0.244 inch;  
Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;  
Adancime: 78,7 mm / 3.098 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,188; MJ  
Greutate: 11,5; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821230793;  
Customs tariff number: 85369010000;  
Pret: 32,24 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/component-terminal-block-4-conductor-with-diode-1n5408-anode-left-side-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-push-in-cage-clamp-4-00-mm2-gray-142440>