

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO T-DISTRIBUTION CONNECTOR; 2-POLE; COD. E; 1 INPUT; 2
OUTPUTS; GREEN**

Note on Contact Resistance: $i \geq p$ approx. 3m Ω , contact resistance

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 50; V
Tensiune nominala de supratensiune (III/3): 0,8; kV
Curent nominal: 3; A
Legend (ratings): (III / 3) $\hat{=}$ Overvoltage category III / Pollution degree 3;
Numar poli: 2;
Total number of potentials: 2;
Latime: 15 mm / 0.591 inch;
Inaltime: 28,9 mm / 1.138 inch;
Adancime: 28,7 mm / 1.13 inch;
Technologie: KNX;
Coding: E;
Mating force of a plug-in connection: approx. 10 ... 15 N;
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;
Number of mating cycles: $i \geq 200$;
Distributor type: T-distribution connector;
Marking: 1+ 2-;
Protection type: IP20;
Note on protection type: Only when mated and secured with a strain relief housing
(These compact connectors are not designed for use in open, easily accessible areas.);
Potential marking: 1+ 2-;
Application: KNX;
Tip contact (pluggable connector): Socket/plug;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: green;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper alloy (surface-treated);
Greutate: 3,3; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ≤ 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454547677;
Customs tariff number: 85366990990;
Pret: 48,31 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/t-distribution-connector-2-pole-cod-e-1-input-2-outputs-green-142549>