


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p><u>WAGO 4-CONDUCTOR SENSOR TERMINAL BLOCK; FOR PNP (POSITIVE) SWITCHING SENSORS; FOR FUSE PLUGS; WITH GRAY END PLATE; WITH COLORED CONDUCTOR ENTRIES; 2.5 MM²; CAGE CLAMP[®]; 2,50 MM²; GRAY</u></p> <p>Tesiune nominala (III/3): 125; V Curent nominal: 5; A Tensiune nominala (III/3) 2: 250; V Curent nominal 2: 6,3; A Legend (ratings): (III / 3) %TM Overvoltage category III / Pollution degree 3; Tehnologie conexiune: CAGE CLAMP[®]; Tip actionare: Operating tool; Connectable conductor materials: Copper; Aluminum; Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Numar total de conexiuni: 6; Total number of potentials: 5; Numar nivele: 4; Wiring type: Front-entry wiring; Note (conductor cross-section): 12 AWG: THHN, THWN; Latime: 6 mm / 0.236 inch; Inaltime from upper-edge of DIN-rail: 63,5 mm / 2.5 inch; Adancime: 90,5 mm / 3.563 inch; Design: angled; Tip montaj: DIN-35 rail; Marking level: Center marking; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Fire load: 0,348; MJ Greutate: 21; g Product Group: 1 (Rail Mounted Terminal Blocks); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454559489; Customs tariff number: 85369010000; Pret: 35,27 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/4-conductor-sensor-terminal-block-for-pnp-positive-switching-sensors-for-fuse-plugs-with-gray-end-plate-with-colored-conductor-entries-2-5-mm2-cage-clamp-2-50-mm2-gray-142997</p>
---	--