

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO TAP-OFF MODULE; 5 X 4 MM<sup>2</sup>; WITH SPRING CLAMP  
CONNECTION; SCREW CONNECT. TO CABLE 5 X 10 MM<sup>2</sup>;  
TRANSPARENT**

Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ;,  
contact transition plug/socket;  
Ratings per: IEC/EN 60664-1;  
Tesiune nominala (III/3): 690; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) â‰™ Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Numar poli: 5;  
Numar total de conexiuni: 5;  
Total number of potentials: 5;  
Latime: 51 mm / 2.008 inch;  
Inaltime: 48 mm / 1.89 inch;  
Adancime: 110 mm / 4.331 inch;  
Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);  
Retention force of a plug-in connection: When locked: > 80 N;  
Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;  
Number of mating cycles: î»¿200, without resistive load 100, with resistive load IN = 25  
A, tested (4 mm<sup>2</sup>/AWG 12);  
Protection type: IP20;  
Note on protection type: Only when mated (these compact connectors are not designed  
for use in open, easily accessible areas).;  
Suitable: for flat cable 5 x 10 mm<sup>2</sup>;  
Mismating protection: Yes;  
Locking of plug-in connection: locking lever;  
Culoare: transparent;  
Material izolator: Polyamide 66 (PA 66);  
Contact material: Copper or copper alloy (surface-treated);  
Fire load: 2,232; MJ  
Greutate: 171,8; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C  
(including halogen-free) PVC flat cable for temperatures -15 °C to ≤ 70 °C (including  
halogen-free) Insulating parts for temperatures ≤ 105 °C;  
Product Group: 20 (WINSTA);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4045454006266;  
Customs tariff number: 85369010000;  
Pret: 192,41 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/tap-off-module-5-x-4-mm2-with-spring-clamp-connection-screw-connect-to-cable-5-x-10-mm2-transparent-143453>