


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO PCB TERMINAL BLOCK; 1.5 MM²; PIN SPACING 3.5 MM; 10-
 POLE; CAGE CLAMP[®]; CLAMPING COLLAR; 1.50 MM²; GRAY**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 160; V
 Tensiune nominala de supratensiune (III/3): 2,5; kV
 Tensiune nominala (III/2): 160; V
 Tensiune nominala de supratensiune (III/2): 2,5; kV
 Tensiune nominala (II/2): 320; V
 Tensiune nominala de supratensiune (II/2): 2,5; kV
 Curent nominal: 17,5; A
 Legend (ratings): (III / 2) \hat{a} %[™] Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 300; V
 Curent nominal UL (Use Group B): 15; A
 Tensiune nominala UL (Use Group D): 300; V
 Curent nominal UL (Use Group D): 10; A
 Certificari: UL 1059;
 Tehnologie conexiune: CAGE CLAMP[®];
 Tip actionare: Operating tool;
 Solid conductor: 0,08 ... 1,5 mm² / 28 ... 14 AWG;
 Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 14 AWG;
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 1 mm²;
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1,5 mm²;
 Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;
 Conductor connection direction to PCB: 90; °
 Numar poli: 10;
 Numar total de conexiuni: 10;
 Total number of potentials: 10;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 1;
 Note (conductor cross-section): 14 AWG: THHN, THWN;
 Distanta intre pini: 3,5 mm / 0.138 inch;
 Latime: 49,8 mm / 1.961 inch;
 Inaltime: 15,7 mm / 0.618 inch;
 Inaltime de la fata: 12,3 mm / 0.484 inch;
 Adancime: 13,4 mm / 0.528 inch;
 Lungimea pinului de contact: 3,4; mm
 Solder pin dimensions: 0,6 x 0,8 mm;
 Diametrul de gaurire cu toleranta: 1,1 (+0,1) mm;
 Tip montaj: Mounting flange;
 Tip montaj: Panel mounting;
 PCB contact: THT;
 Solder pin arrangement: over the entire terminal strip (in-line);
 Number of solder pins per potential: 1;
 Culoare: gray;
 Material group: I;
 Material izolator: Polyamide 66 (PA 66);
 Flammability class per UL94: V0;
 Clamping spring material: Chrome nickel spring steel (CrNi);
 Contact material: Cupru electrolitic (ECu);
 Contact plating: tin-plated;
 Fire load: 0,138; MJ
 Greutate: 7,3; g
 Temperatura lucru: -60 ... +105 °C;
 Product Group: 4 (Printed Circuit);
 Tip ambalare: BOX;
 Tara de origine: PL;
 GTIN: 4017332750233;
 Customs tariff number: 85369010000;
 Pret: 21,65 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pcb-terminal-block-1-5-mm2-pin-spacing-3-5-mm-10-pole-cage-clamp-clamping-collar-1-50-mm2-gray-143531>