

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; 4-POLE;  
PE-N-L1-L2; WITH GROUND CONTACT; FOR 3 MM Ø SCREW AND  
NUT; 4 MM<sup>2</sup>; 4,00 MM<sup>2</sup>; BLACK**

Tesiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) %<sup>o</sup>™ Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Operating tool; Push-button;  
Connectable conductor materials: Copper;  
Solid conductor: 0,5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Stranded conductor: 0,5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor: 0,5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,5 ... 2,5 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 0,75 mm<sup>2</sup> / 18 AWG;  
Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;  
Numar poli: 4;  
Numar total de conexiuni: 16;  
Total number of potentials: 4;  
Wiring type: Side-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Distanta intre pini: 12 mm / 0.472 inch;  
Latime: 48 mm / 1.89 inch;  
Inaltime de la fata: 22,3 mm / 0.878 inch;  
Adancime: 35 mm / 1.378 inch;  
Tip montaj: Screw mounting;  
Marking: PE-N-L1-L2;  
Culoare: black;  
Fire load: 0,503; MJ  
Greutate: 28,2; g  
Product Group: 9 (Std. Chassis Mt. Blocks);  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4044918510868;  
Customs tariff number: 85369010000;  
Pret: 18,61 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-chassis-mount-terminal-strip-4-pole-pe-n-l1-l2-with-ground-contact-for-3-mm-oe-screw-and-nut-4-mm2-4-00-mm2-black-143555>