

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 4 MM<sup>2</sup>; WITH TEST PORT; WITHOUT SHIELD CONTACT; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP<sup>®</sup>; 4,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 800; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 25; A  
Legend (ratings): (III / 3)  $\hat{\%}$ ™ Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP<sup>®</sup>;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 3;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 5 mm / 0.197 inch;  
Inaltime from upper-edge of DIN-rail: 29 mm / 1.142 inch;  
Adancime: 73 mm / 2.874 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,147; MJ  
Greutate: 8,7; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918519922;  
Customs tariff number: 85369010000;  
Pret: 8,24 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-through-terminal-block-4-mm2-with-test-port-without-shield-contact-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-4-00-mm2-gray-143585>