

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO SUPPLY MODULE; 5 X 2.5 MM² + 2 X 1.5 MM²; 5-POLE;
COD. I; WITH STRAIN RELIEF HOUSING; 4,00 MM²; BLUE**

Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ;,
contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 25; A
Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Operating tool; Push-in;
Nominal cross-section: 4 mm²;
Solid conductor: 0,5 ... 4 mm² / 20 ... 12 AWG;
Solid conductor; push-in termination: 1,5 ... 4 mm² / 16 ... 12 AWG;
Stranded conductor: 0,5 ... 2,5 mm² / 20 ... 14 AWG;
Fine-stranded conductor: 0,5 ... 4 mm² / 20 ... 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 ... 1,5 mm² / 20 ... 16 AWG;
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm² / 20 ... 14 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 1,5 mm² / 16 AWG;
Strip length: 9 mm / 0.35 inch;
Numar poli: 5;
Tehnologie conexiune 2: IDC;
Numar total de conexiuni: 10;
Total number of potentials: 5;
Latime: 50 mm / 1.969 inch;
Inaltime: 46,5 mm / 1.831 inch;
Adancime: 82,5 mm / 3.248 inch;
Tehnologie: DALI;
Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;
Number of mating cycles: i»¿200, without resistive load 100, with resistive load IN = 25
A, tested (4 mm²/AWG 12);
Marking: N â‰‰ L DA- DA+;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed
for use in open, easily accessible areas.);
Potential marking: N â‰‰ L DA- DA+;
Application: Lighting management;
Suitable: for flat cable 5 x 2.5 mm², 5 x 4 mm², 5 x 2.5 mm² + 2 x 1.5 mm²;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Fire load: 2,288; MJ
Greutate: 95; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C
(including halogen-free) PVC flat cable for temperatures -15 °C to ≤ 70 °C (including
halogen-free) Insulating parts for temperatures ≤ 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: not packed;
Tara de origine: DE;
GTIN: 4055143174671;
Customs tariff number: 85366990990;
Pret: 97,07 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/supply-module-5-x-2-5-mm2-2-x-1-5-mm2-5-pole-cod-i-with-strain-relief-housing-4-00-mm2-blue-143744>