


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO T-DISTRIBUTION CONNECTOR; 3-POLE; COD. A; 1 INPUT; 2  
OUTPUTS; 2 LOCKING LEVERS; WHITE**

Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket;  
Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Curent nominal: 16; A  
Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL 1977: 600; V  
Curent nominal UL 1977: 14; A  
Numar poli: 3;  
Total number of potentials: 3;  
Ground function: with preceding ground contact;  
Distanta intre pini: 4,4 mm / 0.173 inch;  
Latime: 17,9 mm / 0.705 inch;  
Inaltime: 34 mm / 1.339 inch;  
Adancime: 53,9 mm / 2.122 inch;  
Coding: A;  
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);  
Retention force of a plug-in connection: When locked: > 80 N;  
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);  
Number of mating cycles: î»¿200, without resistive load100, with resistive load IN = 16 A, tested (1.5mm<sup>2</sup>/AWG 16);  
Distributor type: T-distribution connector;  
Marking: L â‰š N;  
Protection type: IP20;  
Note on protection type: IP40 when mated;  
Potential marking: L â‰š N;  
Application: General mains applications;  
Tip contact (pluggable connector): Socket/plug;  
Mismatching protection: Yes;  
Locking of plug-in connection: locking lever;  
Locking lever: yes;  
Culoare: white;  
Material izolator: Polyamide 66 (PA 66);  
Contact material: Copper or copper alloy (surface-treated);  
Fire load: 0,156; MJ  
Greutate: 7,9; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: Insulating parts for temperatures ≤ 105 °C;  
Product Group: 20 (WINSTA);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454490508;  
Customs tariff number: 85366990990;  
Pret: 20,84 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/t-distribution-connector-3-pole-cod-a-1-input-2-outputs-2-locking-levers-white-143776>