


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 3-CONDUCTOR SENSOR SUPPLY TERMINAL BLOCK; FOR PNP (POSITIVE) SWITCHING SENSORS; POWER SUPPLY FROM CONTROL PANEL SIDE; WITH COLORED CONDUCTOR ENTRIES; 2.5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 2,50 MM<sup>2</sup>; ORANGE**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 250; V  
Curent nominal: 28; A  
Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL (Use Group C): 300; V  
Curent nominal UL (Use Group C): 20; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group C): 300; V  
Curent nominal CSA (Use Group C): 20; A  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Push-in; Open Tool Slot;  
Connectable conductor materials: Copper;  
Nominal cross-section: 1 mm<sup>2</sup>;  
Solid conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;  
Solid conductor; push-in termination: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 16 AWG;  
Fine-stranded conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;  
Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;  
Solid conductor 2: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Solid conductor, push-in termination 2: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Fine-stranded conductor 2: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Numar total de conexiuni: 8;  
Total number of potentials: 2;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;  
Latime: 7 mm / 0.276 inch;  
Inaltime from upper-edge of DIN-rail: 49,4 mm / 1.945 inch;  
Adancime: 81,1 mm / 3.193 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: orange;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 15,8; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143497121;  
Customs tariff number: 85369010000;  
Pret: 33,37 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-sensor-supply-terminal-block-for-pnp-positive-switching-sensors-power-supply-from-control-panel-side-with-colored-conductor-entries-2-5-mm2-push-in-cage-clamp-2-50-mm2-orange-143810>