


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO THR MALE HEADER; 0.8 X 0.8 MM SOLDER PIN; STRAIGHT;  
100% PROTECTED AGAINST MISMATING; IN TAPE-AND-REEL  
PACKAGING; PIN SPACING 2.5 MM; 8-POLE; BLACK**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 80; V  
Tensiune nominala de supratensiune (III/3): 2,5; kV  
Tensiune nominala (III/2): 160; V  
Tensiune nominala de supratensiune (III/2): 2,5; kV  
Tensiune nominala (II/2): 320; V  
Tensiune nominala de supratensiune (II/2): 2,5; kV  
Curent nominal: 6; A  
Legend (ratings): (III / 2)  $\hat{=}$  Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group B): 150; V  
Curent nominal UL (Use Group B): 4; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group B): 150; V  
Curent nominal CSA (Use Group B): 4; A  
Numar poli: 8;  
Total number of potentials: 8;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Distanta intre pini: 2.5 mm / 0.098 inch;  
Latime: 22.5 mm / 0.886 inch;  
Inaltime: 11.3 mm / 0.445 inch;  
Inaltime de la fata: 8.9 mm / 0.35 inch;  
Adancime: 7.8 mm / 0.307 inch;  
Lungimea pinului de contact: 2,4; mm  
Solder pin dimensions: 0.8 x 0.8 mm;  
Diametru placat prin gaura (THR): 1.2 (+0.1) mm;  
Reel diameter of tape-and-reel packaging: 330; mm  
Tape Latime: 44; mm  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for PCBs;  
Mismating protection: Yes;  
Mating direction to the PCB: 90; °  
PCB contact: THR;  
Solder pin arrangement: over the entire male connector, in line;  
Number of solder pins per potential: 1;  
Culoare: black;  
Material group: I;  
Material izolator: Polyphthalamide (PPA GF);  
Flammability class per UL94: V0;  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,028; MJ  
Greutate: 1,6; g  
Temperatura lucru: -60 ... +100 °C;  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4045454774394;  
Customs tariff number: 85366990990;  
Pret: 14,21 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/thr-male-header-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismating-in-tape-and-reel-packaging-pin-spacing-2-5-mm-8-pole-black-143871>