


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 16 MM<sup>2</sup>;  
SUITABLE FOR EX E II APPLICATIONS; CENTER MARKING; FOR DIN-  
RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 16,00 MM<sup>2</sup>; LIGHT  
GRAY**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala EN (Ex e II): 550; V  
Curent nominal (Ex e II): 68; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Fine-stranded conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Strip length: 16 ... 17 mm / 0.63 ... 0.67 inch;  
Numar total de conexiuni: 3;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 12 mm / 0.472 inch;  
Inaltime from upper-edge of DIN-rail: 37,5 mm / 1.476 inch;  
Adancime: 104,5 mm / 4.114 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: light gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,619; MJ  
Greutate: 45,3; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918543712;  
Customs tariff number: 85369010000;  
Pret: 28,06 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-through-terminal-block-16-mm2-suitable-for-ex-e-ii-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-16-00-mm2-light-gray-144160>