


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><u>WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; ECA; SOCKET/PLUG; 3-POLE; COD. A; H05VV-F 3G 2.5 MM²; 5 M; 2,50 MM²; WHITE</u></p> <p>Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tesiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 20; A Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Numar poli: 3; Total number of potentials: 3; Ground function: with preceding ground contact; Conductor preparation: tip-bonded; Sheathed cable diameter: 9,2 ... 11,4 mm; Sectiunea transversala a firului: 2,5; mm² Connection type: Socket - Plug; Total length: 5; m Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number); Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 30 ... 70 N (depending on pole number); Number of mating cycles: î»¿200, without resistive load100, with resistive load IN = 20 A, tested (2.5mm²/AWG 14); Connection type: Socket - Plug; Type of pre-assembled cable: Interconnecting cable; Cable type: H05VV-F 3G2.5; Marking: L â‰š N; Protection type: IP20; Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas.); Application: General mains applications; Mismating protection: Yes; Locking of plug-in connection: locking lever; Culoare: white; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper or copper alloy (surface-treated); Fire load: 13,466; MJ Connector Culoare: white; Strain relief Culoare: white; Sheath material: PVC; Greutate: 808,6; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: DE; GTIN: 4045454320737; Customs tariff number: 85444290900; Pret: 87,99 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/pre-assembled-interconnecting-cable-eca-socket-plug-3-pole-cod-a-h05vv-f-3g-2-5-mm2-5-m-2-50-mm2-white-144285</p>
---	--