


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><b>WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; ECA; SOCKET/PLUG; 2-POLE; COD. E; J-Y(ST)YÄ€;LG 2X2X0.8; 5 M; GREEN</b></p> <p>Note on Contact Resistance: <math>i \gg \zeta &lt; p &gt;</math> approx. 3mâ„¸, contact resistance <math>&lt; /p &gt;</math>; Ratings per: IEC/EN 60664-1; Tesiune nominala (III/3): 50; V Tensiune nominala de supratensiune (III/3): 0,8; kV Curent nominal: 3; A Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Conductor diameter: 0,8 mm; Numar poli: 2; Total number of potentials: 2; Conductor preparation: tip-bonded; Connection type: Socket - Plug; Total length: 5; m Technologie: KNX; Coding: E; Mating force of a plug-in connection: approx. 10 ... 15 N; Retention force of a plug-in connection: when locked: &gt; 80N; Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N; Number of mating cycles: <math>i \gg \zeta 200</math>; Connection type: Socket - Plug; Type of pre-assembled cable: Interconnecting cable; Cable type: UNITRONIC BUS EIB 2x2x0.8; Marking: 1+ 2-; Protection type: IP20; Note on protection type: Only when mated and secured with a strain relief housing (These compact connectors are not designed for use in open, easily accessible areas.); Potential marking: 1+ 2-; Application: KNX; Mismating protection: Yes; Locking of plug-in connection: locking lever; Culoare: green; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper alloy (surface-treated); Fire load: 4,663; MJ Connector Culoare: green; Strain relief Culoare: black; Sheathed cable Culoare: green; Halogen-free: Yes; Greutate: 280,7; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures <math>\leq 70</math> °C (including halogen-free) Insulating parts for temperatures <math>\leq 105</math> °C; Tip ambalare: not packed; Tara de origine: PL; GTIN: 4055143306737; Customs tariff number: 85444290900; Pret: 152,17 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/pre-assembled-interconnecting-cable-eca-socket-plug-2-pole-cod-e-j-y-st-y-ä€-lg-2x2x0-8-5-m-green-144308">https://www.materialelectrice.ro/pre-assembled-interconnecting-cable-eca-socket-plug-2-pole-cod-e-j-y-st-y-ä€-lg-2x2x0-8-5-m-green-144308</a></p>
---	---