


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO 1-CONDUCTOR THT FEMALE HEADER; 1.4 MM Å~ SOLDER
 PIN; ANGLED; DIRECT MARKING; 2.5 MMÅ²; PIN SPACING 5 MM; 10-
 POLE; 2,50 MMÅ²; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 250; V
 Tensiune nominala de supratensiune (III/3): 4; kV
 Tensiune nominala (III/2): 320; V
 Tensiune nominala de supratensiune (III/2): 4; kV
 Tensiune nominala (II/2): 630; V
 Tensiune nominala de supratensiune (II/2): 4; kV
 Curent nominal: 16; A
 Legend (ratings): (III / 2) â‰‰™ Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 300; V
 Curent nominal UL (Use Group B): 15; A
 Tensiune nominala UL (Use Group D): 300; V
 Curent nominal UL (Use Group D): 10; A
 Certificari: UL 1059;
 Tehnologie conexiune: Push-in CAGE CLAMP®;
 Tip actionare: Push-button;
 Solid conductor: 0,2 ... 2,5 mm² / 24 ... 12 AWG;
 Fine-stranded conductor: 0,2 ... 2,5 mm² / 24 ... 12 AWG;
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 1,5 mm²;
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²;
 Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;
 Conductor connection direction to PCB: 0; °
 Numar poli: 10;
 Numar total de conexiuni: 10;
 Total number of potentials: 10;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 1;
 Distanta intre pini: 5 mm / 0.197 inch;
 Latime: 50 mm / 1.969 inch;
 Inaltime: 13,4 mm / 0.528 inch;
 Adancime: 15,4 mm / 0.606 inch;
 Lungimea pinului de contact: 3,6; mm
 Diametrul pinului de contact: 1,4; mm
 Diametrul de gaurire cu toleranta: 1,6 (+0,1) mm;
 Tip contact (pluggable connector): Conector mama/priza;
 Connector (connection type): for PCB;
 Mismatching protection: No;
 Mating direction to the PCB: 0; °
 PCB contact: THT;
 Culoare: light gray;
 Material group: I;
 Material izolator: Polyphthalamide (PPA GF);
 Flammability class per UL94: V0;
 Clamping spring material: Chrome nickel spring steel (CrNi);
 Contact material: Cupru electrolitic(ECu);
 Contact plating: tin-plated;
 Fire load: 0,229; MJ
 Greutate: 11,7; g
 Temperatura lucru: -60 ... +100 °C;
 Product Group: 26 (picoMAX);
 Tip ambalare: BOX;
 Tara de origine: DE;
 GTIN: 4050821358459;
 Customs tariff number: 85366990990;
 Pret: 36,90 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-tht-female-header-1-4-mm-oe-solder-pin-angled-direct-marking-2-5-mm2-pin-spacing-5-mm-10-pole-2-50-mm2-light-gray-144327>