

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p>WAGO 1-CONDUCTOR FEMALE PLUG; GRIPPING PLATE; DIRECT MARKING; 2.5 MM²; PIN SPACING 5 MM; 10-POLE; 2,50 MM²; LIGHT GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) \hat{a}%TM Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-button; Solid conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm²; Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch; Numar poli: 10; Numar total de conexiuni: 10; Total number of potentials: 10; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 5 mm / 0.197 inch; Latime: 50 mm / 1.969 inch; Inaltime: 40.4 mm / 1.591 inch; Adancime: 13.4 mm / 0.528 inch; Design: With gripping plate; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for conductors; Mismatching protection: No; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ESu); Contact plating: tin-plated; Fire load: 0,263; MJ Greutate: 10,9; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821353546; Customs tariff number: 85366990990; Pret: 35,10 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/1-conductor-female-plug-gripping-plate-direct-marking-2-5-mm2-pin-spacing-5-mm-10-pole-2-50-mm2-light-gray-144426</p>
--	---