

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO SOLDER PIN STRIP; 1.0 MM $\tilde{\sim}$ SOLDER PIN; ANGLED; PIN SPACING 3.5 MM; 2-POLE; BLACK</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 160; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) $\hat{\%}$™ Overvoltage category III / Pollution degree 2; Certificari: UL 1059; Numar poli: 2; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 3.5 mm / 0.138 inch; Latime: 8.7 mm / 0.343 inch; Inaltime: 5.9 mm / 0.232 inch; Inaltime de la fata: 3.5 mm / 0.138 inch; Adancime: 10.2 mm / 0.402 inch; Lungimea pinului de contact: 2,4; mm Diametrul pinului de contact: 1; mm Diametru placat prin gaura (THR): 1.2 (+0.1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCBs; Mismatching protection: No; Mating direction to the PCB: 0; ° PCB contact: THR; Culoare: black; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Greutate: 0,2; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: bag; Tara de origine: CN; GTIN: 4055143935722; Customs tariff number: 85369010000; Pret: 2,15 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/solder-pin-strip-1-0-mm-oe-solder-pin-angled-pin-spacing-3-5-mm-2-pole-black-144454</p>
--	--