

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO THR MALE HEADER; 1.0 MM <math>\tilde{\sim}</math> SOLDER PIN; ANGLED; CLAMPING COLLAR; PIN SPACING 3.5 MM; 5-POLE; LIGHT GRAY</b></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 160; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) <math>\hat{\sim}</math>™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Numar poli: 5; Total number of potentials: 5; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 3,5 mm / 0.138 inch; Latime: 31,5 mm / 1.24 inch; Inaltime: 14,8 mm / 0.583 inch; Inaltime de la fata: 12,4 mm / 0.488 inch; Adancime: 17,5 mm / 0.689 inch; Lungimea pinului de contact: 2,4; mm Diametrul pinului de contact: 1; mm Diametru placat prin gaura (THR): 1,2 (+0,1) mm; Tip montaj: Mounting flange; Tip montaj: Feed-through mounting; Panel mounting; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCB; Mismatching protection: No; Mating direction to the PCB: 0; ° Locking of plug-in connection: Locking latch; PCB contact: THR; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic (ECu); Contact plating: tin-plated; Fire load: 0,054; MJ Greutate: 2,3; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821396321; Customs tariff number: 85366990990; Pret: 7,58 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/thr-male-header-1-0-mm-oe-solder-pin-angled-clamping-collar-pin-spacing-3-5-mm-5-pole-light-gray-144494">https://www.materialelectrice.ro/thr-male-header-1-0-mm-oe-solder-pin-angled-clamping-collar-pin-spacing-3-5-mm-5-pole-light-gray-144494</a></p>
--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------