


Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**WAGO 1-CONDUCTOR THT FEMALE HEADER; 1.0 MM  $\hat{\sim}$  SOLDER  
 PIN; STRAIGHT; GRIPPING PLATE; DIRECT MARKING; 1.5 MM $\hat{\sim}$  PIN  
 SPACING 3.5 MM; 8-POLE; 1,50 MM $\hat{\sim}$ ; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;  
 Tensiune nominala (III/3): 160; V  
 Tensiune nominala de supratensiune (III/3): 2,5; kV  
 Tensiune nominala (III/2): 160; V  
 Tensiune nominala de supratensiune (III/2): 2,5; kV  
 Tensiune nominala (II/2): 320; V  
 Tensiune nominala de supratensiune (II/2): 2,5; kV  
 Curent nominal: 10; A  
 Legend (ratings): (III / 2)  $\hat{\sim}$ ™ Overvoltage category III / Pollution degree 2;  
 Tensiune nominala UL (Use Group B): 300; V  
 Curent nominal UL (Use Group B): 10; A  
 Tensiune nominala UL (Use Group D): 300; V  
 Curent nominal UL (Use Group D): 10; A  
 Certificari: UL 1059;  
 Tehnologie conexiune: Push-in CAGE CLAMP®;  
 Tip actionare: Push-button;  
 Solid conductor: 0,2 ... 1,5 mm $\hat{\sim}$  / 24 ... 14 AWG;  
 Fine-stranded conductor: 0,2 ... 1,5 mm $\hat{\sim}$  / 24 ... 14 AWG;  
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 0,75 mm $\hat{\sim}$ ;  
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1,5 mm $\hat{\sim}$ ;  
 Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
 Conductor connection direction to PCB: 90; °  
 Numar poli: 8;  
 Numar total de conexiuni: 8;  
 Total number of potentials: 8;  
 Numar tipuri de conexiuni: 1;  
 Numar nivele: 1;  
 Distanta intre pini: 3,5 mm / 0.138 inch;  
 Latime: 28 mm / 1.102 inch;  
 Inaltime: 33 mm / 1.299 inch;  
 Adancime: 11,4 mm / 0.449 inch;  
 Lungimea pinului de contact: 3,6; mm  
 Diametrul pinului de contact: 1; mm  
 Diametrul de gaurire cu toleranta: 1,2 (+0,1) mm;  
 Design: With gripping plate;  
 Tip contact (pluggable connector): Conector mama/priza;  
 Connector (connection type): for PCB;  
 Mismatching protection: No;  
 Mating direction to the PCB: 90; °  
 PCB contact: THT;  
 Culoare: light gray;  
 Material group: I;  
 Material izolator: Polyphthalamide (PPA GF);  
 Flammability class per UL94: V0;  
 Clamping spring material: Chrome nickel spring steel (CrNi);  
 Contact material: Cupru electrolitic(ESu);  
 Contact plating: tin-plated;  
 Fire load: 0,094; MJ  
 Greutate: 4,6; g  
 Temperatura lucru: -60 ... +100 °C;  
 Tip ambalare: BOX;  
 Tara de origine: DE;  
 GTIN: 4050821366881;  
 Customs tariff number: 85366990990;  
 Pret: 29,91 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-tht-female-header-1-0-mm-oe-solder-pin-straight-gripping-plate-direct-marking-1-5-mm2-pin-spacing-3-5-mm-8-pole-1-50-mm2-light-gray-144580>