

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p><u>WAGO THR PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 6 MM; 1-POLE; PUSH-IN CAGE CLAMP®; IN TAPE-AND-REEL PACKAGING; 1.50 MM²; WHITE</u></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 17,5; A Legend (ratings): (III / 2) $\hat{a}\%$™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 600; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 600; V Curent nominal UL (Use Group D): 5; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-button; Solid conductor: 0,5 ... 1,5 mm² / 20 ... 16 AWG; Fine-stranded conductor: 0,5 ... 1,5 mm² / 20 ... 16 AWG; Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm²; Fine-stranded conductor; with uninsulated ferrule: 0,5 ... 0,75 mm²; Strip length: 7 ... 10 mm / 0.28 ... 0.39 inch; Conductor connection direction to PCB: 0; ° Numar poli: 1; Numar total de conexiuni: 1; Total number of potentials: 1; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 6 mm / 0.24 inch; Latime: 5,7 mm / 0.224 inch; Inaltime: 7,1 mm / 0.28 inch; Inaltime de la fata: 5,6 mm / 0.22 inch; Adancime: 15,2 mm / 0.598 inch; Lungimea pinului de contact: 1,5; mm Solder pin dimensions: 1,2 x 0,35 mm; Diametru placat prin gaura (THR): 1,5 (+0,1) mm; Reel diameter of tape-and-reel packaging: 330; mm Tape Latime: 24; mm PCB contact: THR; Solder pin arrangement: within the terminal block (in-line); Number of solder pins per potential: 2; Culoare: white; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Greutate: 0,5; g Temperatura lucru: -60 ... +105 °C; Tip ambalare: BOX; Tara de origine: CH; GTIN: 4055143274722; Customs tariff number: 85369010000; Pret: 3,70 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/thr-pcb-terminal-block-push-button-1-5-mm2-pin-spacing-6-mm-1-pole-push-in-cage-clamp-in-tape-and-reel-packaging-1-50-mm2-white-144606</p>
--	---