

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 95 MM<sup>2</sup>;**  
**LATERAL MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL; POWER**  
**CAGE CLAMP; 95,00 MM<sup>2</sup>; GRAY**

Voltage type 1: AC/DC;  
Voltage type 2: DC;  
Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 1000; V  
Tensiune nominala de supratensiune (III/3): 12; kV  
Curent nominal: 232; A  
Tensiune nominala (III/3) 2: 1500; V  
Tensiune nominala de supratensiune (III/3) 2: 12; kV  
Legend (ratings): (III / 3)  $\hat{\%}$ ™ Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: POWER CAGE CLAMP;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 25 ... 95 mm<sup>2</sup> / 4 ... 4/0 AWG;  
Stranded conductor: 25 ... 95 mm<sup>2</sup> / 4 ... 4/0 AWG;  
Fine-stranded conductor: 25 ... 95 mm<sup>2</sup> / 4 ... 4/0 AWG;  
Strip length: 35 mm / 1.38 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 25 mm / 0.984 inch;  
Inaltime from upper-edge of DIN-rail: 101 mm / 3.976 inch;  
Adancime: 107 mm / 4.213 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 3,564; MJ  
Greutate: 264,3; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918452564;  
Customs tariff number: 85369010000;  
Pret: 149,98 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-95-mm2-lateral-marker-slots-only-for-din-35-x-15-rail-power-cage-clamp-95-00-mm2-gray-144666>