

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR  
SOLID CONDUCTORS; MAX. 4 MM<sup>2</sup>; 4-CONDUCTOR; BROWN CLEAR  
HOUSING; RED COVER; SURROUNDING AIR TEMPERATURE: MAX  
60°C; 2,50 MM<sup>2</sup>**

Ratings per: IEC/EN 60664-1;  
Tesiune nominala (II/2): 400; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 32; A  
Legend (ratings): (II / 2) <sup>â</sup>%™ Overvoltage category II / Pollution degree 2;  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Push-in;  
Connectable conductor materials: Copper; Aluminum;  
Strip length: 12 mm / 0.47 inch;  
Numar total de conexiuni: 6;  
Total number of potentials: 1;  
Wiring type: Side-entry wiring;  
Latime: 13 mm / 0.512 inch;  
Inaltime: 13,1 mm / 0.516 inch;  
Adancime: 19,5 mm / 0.768 inch;  
Cover Culoare: red;  
Flammability class per UL94: V2;  
Greutate: 2,4; g  
Surrounding air temperature (operation): 60 °C;  
Continuous operating temperature: 105 °C;  
Product Group: 7 (Push Wire Conn.);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4055143243681;  
Customs tariff number: 85369010000;  
Pret: 2,03 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-conductors-max-4-mm2-4-conductor-brown-clear-housing-red-cover-surrounding-air-temperature-max-60c-2-50-mm2-144678>